

---

---

# **Nipomo Mesa Groundwater Resource Capacity Study, San Luis Obispo County, California**



**S.S. PAPADOPULOS & ASSOCIATES, INC.**  
San Francisco, California

**March 2004**

---

---

# **Nipomo Mesa Groundwater Resource Capacity Study, San Luis Obispo County, California**

*Prepared For:*

**San Luis Obispo County**

*Prepared By:*



**S.S. PAPADOPULOS & ASSOCIATES, INC.**  
**San Francisco, California**

**March 2004**

## Table of Contents

|  | Page        |
|--|-------------|
| <b>Executive Summary .....</b>                                     | <b>ES-1</b> |
| <b>Section 1 Introduction and Background.....</b>                  | <b>1</b>    |
| 1.1 OBJECTIVE AND SCOPE .....                                      | 1           |
| 1.2 ACKNOWLEDGEMENTS.....  | 1           |
| <b>Section 2 Santa Maria Groundwater Basin and Vicinity .....</b>  | <b>2</b>    |
| 2.1 GEOLOGY .....  | 2           |
| 2.2 AQUIFER CHARACTERISTICS.....                                   | 2           |
| 2.3 HISTORICAL PRECIPITATION RECORD.....                           | 3           |
| 2.4 WATERSHEDS AND SURFACE WATER.....                              | 4           |
| 2.5 SANTA MARIA RIVER VALLEY .....                                 | 6           |
| 2.5.1 PROLONGED PERIOD WITH LOW RAINFALL RESULTS IN OVERDRAFT..... | 8           |
| 2.6 GROUNDWATER QUALITY .....                                      | 10          |
| 2.7 GROUNDWATER LEVELS AND FLOW DIRECTIONS .....                   | 10          |
| <b>Section 3 Nipomo Mesa .....</b>                                 | <b>11</b>   |
| 3.1 GEOLOGY AND HYDROGEOLOGY .....                                 | 11          |
| 3.2 GROUNDWATER LEVELS AND FLOW DIRECTIONS .....                   | 12          |
| 3.3 GROUNDWATER BUDGET AND CHANGE IN STORAGE.....                  | 13          |
| 3.4 ESTIMATES OF GROUNDWATER DEMAND AND CAPACITY .....             | 14          |
| 3.5 NIPOMO WATER PLANNING AREA .....                               | 15          |
| 3.6 GROUNDWATER MODELING TO ASSESS IMPACT OF DEVELOPMENT .....     | 17          |
| 3.7 SEA WATER INTRUSION.....                                       | 18          |
| 3.7.1 IDEALIZED FRESHWATER/SALTWATER INTERFACE.....                | 18          |
| 3.7.2 COASTAL MARGIN MONITORING WELLS .....                        | 19          |
| 3.7.3 MODELING TO EVALUATE POTENTIAL SALTWATER INTRUSION .....     | 19          |
| <b>Section 4 Conclusions and Recommendations .....</b>             | <b>21</b>   |
| <b>Section 5 References.....</b>                                   | <b>25</b>   |

## Figures

1. Location Map (Santa Maria GW Basin)
2. Nipomo Water Planning Area (WPA 6) and Subareas
3. Conceptual Geologic Cross-Sections
4. Contour Map of Equal Mean Annual Precipitation
5. Rainfall Records
6. Cumulative Departure from Mean Precipitation
7. Santa Maria and Cuyama Watersheds
8. 10-Year Sliding Window Average Annual Rainfall at Santa Maria
9. Santa Maria River Flow Rate Near Guadalupe  
Number of Days Per Year With Flows Exceeding 1 cfs (1941-1987)
10. Spring 1975 Groundwater Elevation Contours
11. Spring 1985 Groundwater Elevation Contours
12. Spring 1995 Groundwater Elevation Contours
13. Spring 2000 Groundwater Elevation Contours
14. Estimates by DWR of Water Budget Components for Nipomo Mesa
15. Graphic Analysis of DWR Nipomo Mesa Water Budget
16. Coastal Aquifer Conceptual Cross-Section
17. Calculated Position of Saltwater/Freshwater Interface
18. Sea Water Intrusion Monitoring Wells
19. Hydrograph Showing Water Levels Below Sea Level in Well Southwest of Nipomo Mesa
20. Model Results Showing Time Lag Beneath Coastline in Response  
to Pumping 15,000 feet Inland
21. Modeled Salinity Distribution For a Range of Pumping Rates
22. Modeled Increase in Salinity with Time 3000 feet Inland  
in Response to Pumping 15,000 feet Inland

## Appendices

- A Geology of Santa Maria Basin
- B Recharge Rate is Not Equivalent to Safe Yield
- C Hydrographs for Nipomo Mesa Area
- D Summary Documentation of Modeling to Evaluate Saltwater Intrusion

## Executive Summary

The Department of Water Resources (DWR) analyses, water budget estimates, and projections indicate that groundwater pumping in the Nipomo Mesa area is in excess of the dependable yield. Since current and projected pumping beneath Nipomo Mesa exceeds inflow (natural recharge plus subsurface inflow), the Nipomo Mesa portion of the Santa Maria Groundwater Basin is currently in overdraft and projections of future demand indicate increasing overdraft. Some studies conducted for Nipomo Area Environmental Impact Reports have overestimated the sustainable yield of groundwater and underestimated future groundwater declines and potential for seawater intrusion.

DWR defines overdraft as *“the condition of a groundwater basin or subbasin in which the amount of water withdrawn by pumping exceeds the amount of water that recharges the basin over a period of years, during which water supply conditions approximate average conditions.”* The statement in the DWR report that the groundwater basin within San Luis Obispo County is currently not in overdraft because of *“consistent subsurface outflow to ocean and no evidence of sea water intrusion”* is inconsistent with DWR’s definition of overdraft.

DWR’s findings for groundwater beneath the Nipomo Mesa Area are consistent with the County’s Resource Management System Water Supply Criterion, Level of Severity III-- existing demand equals or exceeds the dependable supply.

Although existing and projected future water demand at Nipomo Mesa exceeds sustainable groundwater supply based on local water balance analyses, associated potential impact such as seawater intrusion of the aquifer system is not an imminent threat. Hydraulic analyses indicate that a time lag of many decades is likely before heavy groundwater pumping a few miles from the coast results in evidence of seawater intrusion near the coastline.

Declines of 40 to 60 feet in groundwater levels in Santa Maria River Valley occurred between the mid 1940s and late 1960s. Although increased pumping with agricultural development contributed to the drop in groundwater levels, the most important factor appears to be a decrease in recharge due to a prolonged period from 1945 to 1970 with less than average rainfall.

Analysis of historical rainfall data indicate a 30% likelihood that another 10-year period will occur within the next 100 years with annual rainfall nearly 2 inches below average. This would result in major declines in groundwater levels in the Santa Maria River Valley and Nipomo Mesa accompanied by reduced production capability from many wells, increased energy costs for pumping, and increased risk of seawater intrusion of the aquifers near the coastal margin.

Management response to these findings could include increased use of recycled water, increased importation of supplemental water, implementation of additional conservation measures, and appropriate limits on development.

## **Section 1**

### **Introduction and Background**

Increase in population and development of the Nipomo Mesa area of southern San Luis County (Figures 1 and 2) has led to concern by the County about limitations of groundwater supply on which the area is dependent. A 1979 study by the State of California Department of Water Resources (DWR) entitled *Ground Water in the Arroyo Grande Area*, reported that groundwater levels were declining in all parts of the study area as a consequence of groundwater pumping. In 1993, the DWR began a renewed and expanded study of water resources of the area. The results of the DWR study are presented in a 2002 report entitled *Water Resources of the Arroyo Grande – Nipomo Mesa Area*, which is referred to herein as the 2002 DWR Report.

Work by DWR presented in 2002 report was conducted over a period of several years, and during this time several water resource evaluations were also conducted by consulting firms, some on behalf of developers and some for environmental impact reports (EIRs). The DWR report is a voluminous document and valuable compilation of data, however the basis for some of the conclusions and implications regarding sustainable groundwater pumping beneath Nipomo Mesa remain unclear. Moreover, fundamental differences exist between some of the interpretations and conclusions presented in the 1979 and 2002 DWR reports and water resource assessments by consultants.

#### **1.1 Objective and Scope**

In June 2003, the County retained S.S. Papadopoulos & Associates, Inc. (SSP&A) to conduct a resource capacity study of the Nipomo Mesa area. The objective of the study and this report is to distill relevant information from the DWR report and other water resource assessments of the Nipomo Mesa and vicinity, present an assessment of groundwater resources of the Nipomo Mesa, make recommendations for managing the groundwater resources including appropriate level of severity of depletion of the groundwater resource as part of the County's Resource Management System. In addition to the 2002 DWR Report, SSP&A reviewed numerous documents that pertain to water resources of the Nipomo Mesa and vicinity. A list of references is provided at the end of this report.

#### **1.2 Acknowledgements**

John Hand, Senior Planner was the primary contact for the County. John was helpful throughout the project and his comments on preliminary drafts improved this report. Cynthia Koontz, Christine Ferrara, and Frank Honeycutt with the County Public Works Department provided data and contact information. Cynthia Koontz also wrote a useful summary review of the DWR report.

Lew Rosenberg and Martin Feeney shared ideas on hydrogeology of the area. Tim Cleath and Spencer Harris shared data and provided electronic copies of some of their model figures. Dennis Gibbs and Rob Almy at the Santa Barbara County Water Agency, Meryll Gonzalez, Gerhardt Hubner, and Harvey Packard at the RWQCB, and Jodi Isaacs with the Dunes Center helped by sharing information and providing contacts. Don Eley who is the geological coordinator at Unocal Guadalupe Oil Field and Kristine Schroeder with LFR Levine-Fricke provided copies of reports and data on remediation of the Guadalupe Oil Field.

## **Section 2**

### **Santa Maria Groundwater Basin and Vicinity**

#### **2.1 Geology**

Nipomo Mesa overlies the northwestern portion of and is contiguous with the Santa Maria Groundwater Basin (Figures 1). The Santa Maria Groundwater Basin is the upper, relatively recent and water-bearing portion of the Santa Maria Geologic Depositional Basin, which includes older Tertiary age consolidated rocks. The aquifer system in the basin consists of unconsolidated Plio-Pleistocene alluvial deposits including gravel, sand, silt and clay with total thickness ranging from 200 to nearly 3,000 feet. The underlying consolidated rocks typically yield relatively insignificant quantities of water to wells. Jurassic and Cretaceous age basement complex rocks of the Franciscan and Knoxville Formations unconformably underlie the Tertiary and Quaternary rocks.

The unconsolidated alluvial deposits in the Santa Maria Groundwater Basin comprising the aquifer system include the Careaga Sand, the Paso Robles Formation, the Orcutt Formation, Quaternary Alluvium, and river channel deposits, sediment, terrace deposits and wind-blown dune sands at or near the surface. Figure 3 depicts conceptual geologic cross-sections and stratigraphy of the primary aquifer system of the Santa Maria Groundwater Basin (Morro Group, 1990). Offsets of the basement rocks and aquifer units by faults, which are not represented in these simplistic cross-sections (Figure 3), are represented on geologic cross-sections prepared by DWR (2002). The DWR 2002 report discusses significant differences in water levels on opposite sides of the estimated trace of the Santa Maria River Fault, suggesting that the fault is to some degree a hydraulic barrier along the eastern margin of Nipomo Mesa. The DWR cross-sections are included in Appendix A, which provides a more detailed discussion of the geology of the Santa Maria Geologic basin.

#### **2.2 Aquifer Characteristics**

This summary of aquifer characteristics of the Santa Maria Groundwater Basin is based on a review of several sources of information including the DWR 2002 report, a report on a groundwater flow model and assessment of Santa Maria River Valley groundwater yield (Luhdorff & Scalmanini, 2000), a number of reports regarding development of the

Nipomo Mesa Areas (e.g. Cleath and Associates, 1996a, 1998; ESA 1998). Many of these references rely heavily on estimates of aquifer properties reported by Worts (1951). Estimates of hydraulic conductivity are based on specific capacity values from driller's pumping tests, and aquifer testing conducted on a few wells.

The Santa Maria Groundwater Basin includes the Careaga Sand, Paso Robles Formation, Orcutt Formation, terrace deposits, Quaternary Alluvium, river channel deposits, and dune sand. The Aquifers are generally confined in the western portion of the basin. Focus is on the Paso Robles Formation and Quaternary Alluvium, which are the most important aquifers in the Santa Maria River Valley and Nipomo Mesa areas.

The Paso Robles Formation is the thickest and most extensive aquifer in the basin. The report by Luhdorff and Scalmanini (2000) includes a map with hydraulic conductivity (K) values for the Paso Robles Formation at 20 locations. In the Sisquoc plain, Orcutt Upland, and central Santa Maria River Valley, K ranges from 100 to 400 gpd/ft<sup>2</sup> (13 to 52 ft/d). Values are lower in the western portion of the Santa Maria River Valley and beneath Nipomo Mesa where the reported values range from 15 to 110 gpd/ft<sup>2</sup> (2 to 15 ft/d). The wells are typically screened over hundreds of feet of the Paso Robles Fm, so these values represent bulk averages for the formation.

The Quaternary Alluvium is the most permeable aquifer, although few testing data seem to be available to estimate hydraulic conductivity. Luhdorff & Scalmanini show seven locations with estimates of hydraulic conductivities. As for the Paso Robles Formation, data indicate that the hydraulic conductivity of the Alluvium generally decreases to the west. Values of 4500 gpd/ft<sup>2</sup> (600 ft/d) are typical in the Sisquoc plain, while 2000 gpd/ft<sup>2</sup> (265 ft/d) is typical for the lower portion of the alluvium near Guadalupe. Typical thickness for the Quaternary Alluvium in the Santa Maria River Valley is 100 to 200 feet. Near Guadalupe the upper portion of the alluvium is generally fine-grained and acts as a hydraulic confining layer above the lower alluvium and Paso Robles Fm.

Luhdorff & Scalmanini (2000) report specific yield values in the range of 8 to 13 percent, and assume a reasonable value of storativity of 0.0001 for portions of the aquifers system under confined conditions.

### **2.3 Historical Precipitation Record**

DWR compiled and analyzed long-term precipitation records from 36 stations in San Luis Obispo and Santa Barbara Counties (DWR, 2002) and constructed a map showing contours of equal mean annual precipitation based on records from 1870 to 1995. The DWR rainfall map is included as Figure 4. The long-term average annual rainfall in the northern portion of the Santa Maria Groundwater Basin is approximately 14 inches. The majority of rainfall occurs between November and April. Figure 5 shows historical rainfall records for Santa Maria, Nipomo Mesa, and San Luis Obispo.



Cumulative departure curves are useful for evaluating long-term rainfall trends. Figure 6 shows graphs prepared by DWR of cumulative departure from mean precipitation for three stations: (1) California Polytechnic University, San Luis Obispo, (2) Nipomo, and (3) Santa Maria. As indicated on the graphs, long-term downward sloping trends correspond to prolonged periods of less than average rainfall, and upward sloping trends correspond to prolonged periods of more than average rainfall. Based on the cumulative departure curve for San Luis Obispo rainfall, the DWR report identified three wet-dry cycles of precipitation: 1884-1900, 1901-1934, and 1935-1966. In addition, a fourth wet-dry cycle appears to have begun in 1967. Similar cycles are evident on cumulative departure curves for Nipomo and Santa Maria.

Based on the long-term rainfall data, DWR chose 1984-1995 as the base hydrologic period, which is intended to be representative of long-term conditions and encompass dry, wet, and average years of rainfall. This twelve-year period included the most recent pair of dry and wet trends and begins and ends with a series of wet years. In addition, data are available for the 1984-1995, and the period reflects recent conditions.

## **2.4 Watersheds and surface water**

Most of the Santa Maria Groundwater Basin is within the Santa Maria River Watershed, which extends eastward into the coastal range region and covers nearly 1.2 million acres. The California Rivers Assessment (CARA) program<sup>1</sup> divides the Santa Maria River Watershed into two sub-basins: the Cuyama Basin, which is the upper portion of the watershed, and the Santa Maria, which is the lower portion of the watershed. Figure 7 provides maps showing the extent of each.

The Santa Maria portion of the watershed, which includes the Sisquoc and Santa Maria Rivers, covers an area of 453,777 acres (1,836 sq km) and the average annual precipitation (weighted by area) is 19.7 inches. The Cuyama portion of the watershed covers an area of 732,147 acres (2,963 sq km) and average precipitation is 16.3 inches per year. Average precipitation for these watersheds is greater than that for the northwestern portion of the Santa Maria Groundwater Basin because the watershed boundaries extend further inland and include highlands, which receive the most precipitation.

The Santa Maria River begins at the confluence of the Cuyama and Sisquoc Rivers near the town of Garey and it forms the border between Santa Barbara and San Luis Obispo Counties. The Santa Maria River Valley is the major surface water drainage of the Santa Maria River Watershed and a major source of recharge to the aquifers beneath the valley. The Santa Maria River Channel meanders westward some 20 miles over extensive

---

<sup>1</sup> The California Rivers Assessment (CARA) program is a computer-based data management system designed to give resource managers, policy-makers, landowners, scientists and interested citizens rapid access to essential information and tools with which to make sound decisions about the conservation and use of California's rivers. The website (<http://endeavor.des.ucdavis.edu/newcara/>) and program is managed by the Information Center for the Environment at UC Davis.

permeable alluvial deposits with high infiltration potential on its way to the Pacific Ocean. Flow of water in the Santa Maria River Channel is intermittent, occurring only during periods of high seasonal runoff.

The flows of the Sisquoc River and its tributary creeks have been unimpaired throughout the historical period of record, and stream gauging data for the Sisquoc River near Garey are available since 1942. The Cuyama River, which drains a portion of the Sierra Madre Mountains, has been controlled since 1959 by Twitchell Dam (Figure 1).

The Bureau of Reclamation (BOR) constructed Twitchell Dam during the period from July 1956 to October 1958. BOR reports a total storage capacity behind the dam of 224,300 acre-feet (<http://www.usbr.gov/dataweb/html/santamaria.html>). The Dam is on the Cuyama River about 6 miles upstream from its junction with the Sisquoc River.

After construction, BOR transferred operations to the Santa Barbara County Water Agency. Currently, the Santa Maria River Valley Water Conservation District physically operates the reservoir. Floodwaters of the Cuyama River stored behind the dam are released from the dam as quickly as they can be percolated into the Santa Maria River Valley ground-water basin. An important objective of the operation of the dam is to attempt to prevent salt-water intrusion into the aquifers of the Santa Maria River Valley by helping to increase recharge to groundwater and to maintain outflow to the ocean (<http://www.usbr.gov/dataweb/html/santamaria.html>).

When the Sisquoc and Santa Maria Rivers are no longer flowing from natural run-off, available water from Twitchell Reservoir is slowly released and allowed to seep into the ground as it flows towards the ocean. Because water is released from the dam nearly continuously, Twitchell Reservoir is empty much of the time. The discharge rate is controlled, typically at 12,500 cubic feet per second (cfs). At this flow rate water rarely flows past Bonita School Road crossing, nearly 20 miles from the dam and 3.3 miles east of Guadalupe. Even prior to construction of the dam, water flowed in the river all the way to the mouth at the Pacific Ocean only during extended periods of high runoff.

Water nearly always flows in the last few miles of the Santa Maria River bed downstream of Guadalupe. USGS topographic maps (Guadalupe, Point Sal 1:24,000, and Santa Maria 1:100,000 quadrangles) depict a dry Santa Maria River bed in the vicinity of Guadalupe, but flowing water in the last 4 miles of the river, beginning 1.5 miles downstream of Guadalupe. This is likely a consequence of groundwater discharge to the river near the sea. This portion of the Santa Maria River is a gaining river—it functions as a drain for groundwater in the shallow aquifers in this region. The hydraulic gradient is upward from the deeper confined aquifers to the shallow aquifers so upward leakage of groundwater contributes to the shallow aquifers in this area. Irrigation return flows also contribute water to the river. In addition, small but essentially year-round flow from Orcutt Solomon Creek joins the Santa Maria River at the confluence approximately 1.2 miles upstream from the sea (phone conversation with Dunes Program Manager, <http://www.dunescollaborative.org/index.html>).

## 2.5 Santa Maria River Valley

Gauging data for the Santa Maria River near Guadalupe are available since 1941. During the period from 1941 to 1959, before the construction of Twitchell Dam, the number of days per year that the Santa Maria River near Guadalupe flowed was generally decreasing from an average of 30 days in 1941 to less than 10 days in 1959. As a consequence of management of Cuyama River flows after construction of Twitchell, the 1960 to 1987 record at Guadalupe shows a stabilized trend with an average of 10 days per year with water flowing in the River. This is a consequence of management of flows with the Twitchell Dam.

Major declines in groundwater levels in Santa Maria River Valley wells and decrease of the groundwater hydraulic gradient toward the ocean occurred between the mid 1940s and late 1960s. Drops in water level of 40 to 60 feet were common in wells during this period (e.g. DWR, 2002; Luhdorff & Scalmanini, 2000). Total dissolved solids (TDS) in groundwater east of Guadalupe was less than 1000 mg/l in the 1930s, but increased to greater than 3000 mg/l by 1975 (Santa Barbara County Water Agency, 1996, 1999). Increasing groundwater pumping and possible surface water diversions to support flourishing agricultural development in Santa Maria River Valley contributed to the drop in groundwater levels, decrease in flows in the Santa Maria River, and increase in TDS in groundwater. However, the most important factor appears to be a decrease in recharge due to a prolonged period from 1945 to 1970 with less than average rainfall. Graphs of cumulative departure from mean precipitation (Figure 6) illustrate this period of low rainfall.

Substantial recovery of groundwater levels in the Santa Maria River Valley occurred in the 1970s and 1980s. Management of Cuyama River floodwater flows by Twitchell Dam began in 1959 and is credited with increasing recharge to the Santa Maria River Valley and helping to arrest the decline in groundwater levels. Reported estimates of supplemental recharge since construction of the dam range from 20,000 acre-feet per year (AF/Y) (Dames and Moore, 1991) to 38,000 AF/Y (Luhdorff & Scalmanini, 2000). However, these estimates of supplemental recharge are much too large relative to the Cuyama River Flows. Supplemental recharge due to control of storm water flows cannot exceed the total average flow below the dam, and is likely a relatively small portion of the total average flow. Available gauging data for Cuyama River below Twitchell Dam indicate average annual flow in the range of 35,000 to 39,500 AF/Y.

Prior to, as well as after construction of Twitchell Dam, most of the water in the Santa Maria river infiltrated the Santa Maria Valley prior to reaching the mouth at the Pacific Ocean. River water flowed all the way to the Ocean only during extended periods of high runoff. Even prior to the construction of the dam, this occurred on average only several days per year. Based on comparison of Santa Maria River flow records before and after construction of the dam, we estimate that management of Cuyama River discharge at

Twitchell dam<sup>2</sup> enhances average recharge to the Santa Maria River Valley aquifers by no more than 10,000 to 15,000 acre-feet per year. As is discussed in Section 3.4.1 below, the data indicate that long-term variation of rainfall has had much more influence groundwater levels in Santa Maria than Twitchell Dam.

Luhdorff & Scalmanini (2000) report that hydrographs records for the period from the early 1980s to late 1990s show successive periods of decline and recovery that are not consistent with perennial overdraft<sup>3</sup>. Reported estimates of the annual yield of the basin include 120,000 AF (SB Co, 1996, 2000, 2002; Ahlroth, 1995), and 124,000 during the period 1968-1989, which Luhdorff & Scalmanini (2000) report as the approximate sustainable perennial yield<sup>4</sup>. Based on estimates by Luhdorff & Scalmanini (Figures 4-10, 4-12, Luhdorff & Scalmanini, 2000), average demand (groundwater pumping) in the Santa Maria River Valley was 96,200 AF/Y during the period from 1945 to 1970, and 140,000 AF/Y in 2000.

Water balance evaluations for Santa Maria Groundwater Basin using hydrologic conditions based on 45-year period from 1935 to 1979 are reported to indicate average annual deficits of 6,000 AF for historical water demand conditions, and 20,000 AF for water demands projected into the future from the late 1990s (Santa Barbara County, 1992, 1994, 1996, 2000, 2002). However, this estimated deficit is reduced by importation of water to Santa Barbara County beginning in 1996 from the State Water Project (SWP). Santa Barbara County estimated that 12,000 AF of SWP water were imported to the Santa Maria Groundwater Basin in 1999. This reduces the estimated deficit from 20,000 to 8,000 AF/Y. And if we assume that recharge enhancement by Twitchell Dam of 10,000 AF/Y

---

<sup>2</sup> During the period from 1959 to 1983 reported average annual flow in the Cuyama River below Twitchell Dam flow of the Cuyama River is 35,372 AF/Y (pgs E5-E6, DWR, 2002). Our calculation of average flow based on monthly USGS gauge data for a similar time period is 54.4 cfs or 39,456 AF/Y.

<sup>3</sup> *Groundwater Overdraft* is defined in the glossaries to the California Water Plan Update and California's Groundwater Bulletin 118 – 2003 Update (DWR 1998; DWR 2003) as “the condition of a groundwater basin in which the amount of water withdrawn by pumping exceeds the amount of water that recharges the basin over a period of years during which water supply conditions approximate average conditions.” However, the DWR Nipomo Mesa Report and in the text of the Bulletin 118 – 2003 Update (DWR, 2002; pg 154, DWR 2003), also define groundwater overdraft as a condition of a groundwater *subbasin*.

*Perennial Overdraft* is sustained overdraft over a long period of time.

<sup>4</sup> *Perennial Yield* is defined in the glossary to the California Water Plan Update (DWR, 1998) as the “maximum quantity of water that can be annually withdrawn from a groundwater basin over a long period of time (during which water supply conditions approximate average conditions) without developing an overdraft condition.” We consider *sustainable yield*, *sustainable perennial yield*, *perennial yield*, and *dependable yield* to be equivalent terms. In the glossary to the 2002 Nipomo Mesa report, DWR defines *dependable yield* as the “average quantity of water that can be extracted from an aquifer or groundwater basin over a period of time (during which water supply conditions approximate average conditions) without resulting in adverse effects such as subsidence, sea water intrusion, permanently lowered groundwater levels, or degradation of quality. If water management in the basin changes, the perennial yield of the basin may change.” *Safe yield* also directly implies consideration of negative consequences and is defined in the 2003 update to Bulletin 118 (pg 99, DWR, 2003) as “the amount of groundwater that can be continuously withdrawn from a basin without adverse impact.” Some papers that address a common misconception that safe yield is equivalent to the rate of natural recharge are provided in Appendix B.

directly contributes to yield, then the estimated deficit is erased and instead there is a surplus of 2,000 AF/Y. Table 1 summarizes estimates of yield and demand for year 2000 in Santa Maria Valley.

Clearly, these estimates of a yield, demand, and supplemental yield due to enhanced recharge are not precise numbers. Their accuracies are influenced by many uncertain assumptions. Moreover, the recharge enhancement provided by management of flood water discharge from Twitchell Dam may diminish in the future due to depletion of Cuyama river flows by groundwater pumping in Cuyama Valley (DWR, 2003) and decrease in storage capacity with accumulation of sediment in Twitchell Reservoir (e.g. SAIC et al., 2003). Without the assumed 10,000 AF/Y of enhanced recharge, the estimated projected deficit was 8,000 AF/Y, which is only 6.5% of Lurdorff & Scalmanini's estimate of sustainable perennial yield. In other words, the water balance deficit may be a small fraction of the sustainable yield for *average* rainfall conditions.

**Table 1**  
**Reported Estimates of Annual Groundwater Yield, Demand, and Deficit in Year 2000**  
**Santa Maria River Valley**

| Perennial<br>Yield<br>(AF/Y) | Recharge<br>Enhancement<br>(AF/Y) | SWP<br>Supplement<br>(AF/Y) | Demand<br>in Year<br>2000<br>(AF/Y) | Deficit in<br>Year 2000<br>(AF/Y) |
|------------------------------|-----------------------------------|-----------------------------|-------------------------------------|-----------------------------------|
| 120,000                      | 10,000                            | 12,000                      | 140,000                             | -2,000<br>(surplus)               |

#### *2.5.1 Prolonged Period of Low Rainfall Results in Overdraft*

Regardless of details about basin yield and deficits, the data show that a major decline of groundwater levels (drops of 40 to 60 feet) occurred as a consequence of reduced recharge from the river to the Santa Maria River Valley due to a prolonged period from 1945 to 1970 with less than average precipitation. The average annual rainfall during this 25-year period was 2.11 inches (16%) less than the average (13.60 inches) over the entire historical record (1886-2003). Many hydrographs from wells in the Santa Maria River Valley show that major decline in water levels occurred in the first five or ten years during this 25-year period. Based on the 177-year precipitation record for Santa Maria, we have evaluated the probability of prolonged periods with less than average rainfall in the future, which would again result in major decline of groundwater levels in Santa Maria River Valley.

We calculated sliding window averages (moving average) from Santa Maria precipitation record for a 10-year window. Statistical evaluation of this data set provides a basis for estimating probability of future conditions that would result in a major decline in groundwater levels in Santa Maria River Valley, such as occurred during the period from the 1940s to late 1960s. Figure 8 provides graphic illustration of the data and the statistical summary for 10-year moving average data set. The data indicate that the chance is approximately 30% in the next 100 years that a 10-year period will occur with average annual rainfall nearly 2 inches below average, which would result in a major decline in groundwater in the Santa Maria River Valley.

Moreover, this analysis likely underestimates chances of conditions in the future that would result in a major decline of groundwater levels in the Santa Maria River Valley because current and future water demand is greater than average demand during the historical overdraft period upon which this analysis is based. In addition, future contributions to Santa Maria Groundwater Basin from the Cuyama River may decrease as increasing demands deplete water resources in Cuyama Valley, which has been reported to be in a condition of critical groundwater overdraft<sup>5</sup> (e.g. pg 98, DWR, 2003, and Cuyama Valley Study<sup>6</sup>).

For the period from 1895 to 1947, the average annual natural runoff in the Santa Maria River system was estimated at 90,900 AF (pg 49 and Appendix E, DWR, 2002)<sup>7</sup>. Gauging data for the Santa Maria River near Guadalupe recorded since 1941 indicate a much lower average annual flow of 21,700 AF. Moreover, for the period from 1941 to 1987, the majority of time, flow is zero at Guadalupe. Flow exceeding 1 cubic foot per second (cfs) at Guadalupe only occurs an average of 21 days each year (Figure 9). DWR attributes the decrease in average flow in the Santa Maria River to impoundment of runoff at Twitchell Reservoir and presumably increased recharge with controlled releases.

The record from 1941 to 1959, which is before the construction of Twitchell Dam, the number of days per year that the Santa Maria River near Guadalupe flowed was generally decreasing. A trend line fitted to the data drops from an average of 30 days in 1941 to less than 10 days in 1959. Increasing groundwater pumping near the river due to agricultural development in Santa Maria River Valley likely contributed to this trend. The post-Twitchell Dam record, 1960 to 1987, shows a stabilized trend with an average of 10 days per year with water flowing in the River (Figure 9). This is a consequence of management of flows with the Twitchell Dam. Average annual flow data for this gauging station show the same trends (<http://water.usgs.gov/cgi-bin/wuhuc?huc=18060008>).

---

<sup>5</sup> Definition of *Critical Overdraft* (pg 98, DWR, 2003): “A basin is subject to critical conditions of overdraft when continuation of present water management practices would probably result in significant adverse overdraft-related environmental, social, or economic impacts.”

<sup>6</sup> Cuyama Valley Irrigation Water Management & Groundwater Study conducted by researchers at the UC Davis Information Center for the Environment for the USDA - Natural Resources Conservation Service in cooperation with the Cachuma Resource Conservation District:  
<http://endeavor.des.ucdavis.edu/nrpi/NRPIDescription.asp?ProjectPK=4988>

<sup>7</sup> Original data source: California State Water Resources Board, Bulletin 1, 1951.



The amount of additional recharge provided to the Santa Maria River Valley by management of Cuyama River flows by Twitchell Dam appears to have been overestimated. In addition, both overdraft in Cuyama Basin (e.g. pg 98, DWR, 2003) and decrease in the capacity of Twitchell reservoir caused by accumulation of sediment (SAIC et al., 2003) will reduce the additional recharge to Santa Maria River Valley in the future. Importation of State Water to Santa Maria River Valley has helped avoid overdraft conditions, however, the data indicate that a series of several years with less than average rainfall would lead to significant decline in groundwater levels in the Santa Maria River Valley and accompanying reduced production capability from many wells, increased energy costs for pumping, and increased risk of seawater intrusion of the aquifers near the coastal margin.

## **2.6 Groundwater Quality**

Total dissolved solids (TDS) in groundwater generally increase from east to west. TDS east of Guadalupe <1000 mg/l in the 1930s, but increased to >3000 mg/l by 1975. In the vicinity of Santa Maria and Guadalupe, the basin is classified as vulnerable to nitrate contamination, and in places, concentrations of nitrate have increased from <30 mg/l in 1950s to over 100 mg/l in the 1990s (Santa Barbara County, 1996, 1999). The Careaga Sand, which is the basal member of the system of alluvial aquifers in the basin, is generally considered to have poor water quality (e.g. Dames and Moore, 1991).

## **2.7 Groundwater Levels and Flow Directions**

The California Department of Water Resources began monitoring groundwater levels in some wells in the Santa Maria Groundwater Basin in the 1930s. Most of the available water level data are from pumping wells and usually it is not known if the wells are pumping or idle, or how long pumping was curtailed before making a water level measurement. As a consequence the water level data are of limited value. However, particularly for wells with long records, the general trends can be useful and informative.

Profiles along the Santa Maria River of historical groundwater levels show that major decline of groundwater levels occurred as a result of expansion of irrigated agriculture in the 1920s and 1930s. Prior to the beginning of heavy pumping for irrigation, confined hydraulic groundwater head elevations were 50 to 75 feet higher within a few miles of the coast (e.g. Morro Group, 1996). Over the years, the transition between unconfined and confined conditions has generally migrated westward toward the coast. This means that water levels have dropped below confining intervals (aquitards) so the water is no longer under confined (pressure) conditions. Prior to the decline in water levels, groundwater discharged to the Santa Maria River near the coast, but as hydraulic head in the aquifer dropped contribution near the coast of groundwater to baseflow of the Santa Maria River decreased and the potential for seawater intrusion of the aquifers increased.

General groundwater flow in Santa Maria basin is east to west, from the Sisquoc area toward the ocean. As a consequence of agricultural demands on groundwater in the Santa Maria River Valley, the hydraulic gradient flattened considerably beneath the central and western portions of the basin between the mid-1940s and mid-1960s. Luhdorff & Scalmanini report that since the mid-1960s the flattening of the hydraulic gradient in the SMV has fluctuated and the portion of the Santa Maria Valley along the upper reach of Santa Maria river shows influence of increased recharge due to management of flows by Twitchell Dam.

### **Section 3**

#### **Nipomo Mesa**

##### **3.1 Geology and Hydrogeology**

A mantle of late Pleistocene eolian (wind-blown) dune sands underlies the elevated area, known as Nipomo Mesa. The dune deposits were once much more extensive, but most were eroded away during the last ice age by the ancestral Arroyo Grande Creek, Los Berros Creek, and Santa Maria River. Today the Nipomo Mesa older dune sands is a triangular lobe more than 4 miles wide on the coastal side and extending inland more than 12 miles just east of Hwy 101. Lithologic logs of water wells indicate that the Nipomo Mesa dune sands are 150 to 250 feet thick. The Nipomo Mesa dune sands are very porous and permeable, and very little runoff leaves the Mesa. DWR (2002) reports that little runoff occurs from the bluffs at the margins of Nipomo Mesa, but that increased development has resulted in some increase in runoff from the mesa to the adjacent Arroyo Grande Plain and Santa Maria River Valley.

Groundwater in the dune sands is of relatively minor significance for water supply and the primary aquifer is the underlying Paso Robles Formation where groundwater is in hydraulic continuity with the Santa Maria groundwater basin (e.g. Morro Group, 1996; Cleath and Associates, 1996a, 1998; ESA 1998; DWR, 2000). Hydraulic conductivity of Paso Robles Formation is generally lower beneath Nipomo Mesa and in the western portion of the Santa Maria River Valley relative to the eastern portion; reported values range from 15 to 110 gpd/ft<sup>2</sup> (2 to 15 ft/d) (e.g. Luhdorff & Scalmanini, 2002, Morro Group, 1996, Cleath and Associates 1996a).

The dune sands locally contain clay layers on which groundwater is perched. In addition, fine-grained layers in the upper portion of the Paso Robles Formation beneath dune sands are reported to function as a perching layer (Morro Group, 1996). Some of the shallow groundwater that percolates downward within the permeable Nipomo Mesa dune sands is diverted laterally along these low-permeability layers and discharges into Black Lake Canyon and supports Black Lake and the other systems of coastal drainages and lakes west of Nipomo Mesa including the creek in Cienega Valley, Celery Lakes, White Lake, Little Oso Flaco Lake and the creek along the southwest margin of Nipomo Mesa.



The majority of water demands in the Nipomo Mesa area are supplied with groundwater because there are no significant creeks or rivers. As a consequence DWR (2002) reports that the main source of recharge is percolation of rainfall. However, subsurface inflow from Santa Maria River Valley is also an important component of the groundwater balance of the Nipomo Mesa area.

The amount of recharge to groundwater from precipitation on the Mesa is controversial, and estimates vary wildly—from zero to 100 percent. Cleath and Associates (1996a) estimated that 25% of rainfall on Nipomo Mesa percolates to groundwater, which equates to 5625 AF/Y of recharge over an area of 18,000 acres. However, Cleath and Associates (1997) subsequently advocated that extensive groves of eucalyptus trees intercept essentially all rainfall and prevent any recharge to groundwater for portions of Nipomo Mesa. Removal of gum trees and engineering of suburban runoff should locally increase recharge, but may not make significant difference to recharge to main aquifers on scale of the Nipomo Mesa.

### **3.2 Groundwater Levels and Flow Directions**

Interpretation of groundwater flow directions from groundwater contour maps for the Nipomo Mesa is difficult because in some cases data is included from wells, which are screened within perched groundwater in the dunes, and little information regarding pumping status for wells is available. In addition, groundwater levels are discontinuous across the Santa Maria River Fault, which functions as a partial hydraulic barrier along the northeast margin of the Nipomo Mesa (e.g. Luhdorff & Scalmanini, 2000). In the early 1970s, some groundwater contour maps depicted a general groundwater mound beneath Nipomo Mesa with flow to the south to Santa Maria River Valley, to the northwest toward Arroyo Grande Valley, and to the west toward the sea. In general, however, most groundwater contour maps show westward flow toward the sea.

DWR (2002) presented contour maps of groundwater levels for Spring 1975, 1985, 1995 and 2000, included herein as Figures 10 to 13. These contour maps show that marked depressions associated with heavy pumping beneath parts of Nipomo Mesa have a significant influence on local groundwater flow directions. Based on our review of available water level from specific wells, the 1995 DWR contour map (Figure 12) appears to underestimate the depth and extent of a significant groundwater depression beneath Nipomo Mesa. Static water levels recorded in four wells installed in 1993 and 1994 for the Woodlands project over an area of approximately 4 square miles, are 6 to 31 feet lower (average 14 feet lower) than water levels indicated by the DWR water level contour map for 1995. These water level data are posted on Figure 12.

The County measures water levels twice a year in approximately 85 wells in the San Luis Obispo County portion of the Santa Maria Basin and recently completed compiling historical data and upgrading the database of groundwater elevations. Hydrographs, which depict water level elevation versus time, are provided in Appendix C for 20 wells in the

Nipomo Mesa Area. A line fitted to the entire data record is included on each hydrograph to show general trend in water level over the entire period of record. An overall decreasing trend in water level prevails.

Most wells on Nipomo Mesa with water level elevations greater than 100 feet are likely completed within or across intervals of shallow perched groundwater in the dune deposits. Such wells are not representative of the regional water level in the underlying Paso Robles Formation, which is the primary aquifer.

Based on the County water level database, several of the Nipomo Mesa wells have water levels below 10 feet MSL and a few have water levels below sea level even for non-pumping conditions. Note also, that in most cases the water levels are recorded for non-pumping conditions, and the pumping levels are generally several tens of feet lower.

### **3.3 Groundwater Budget and Change in Storage**

DWR (2002) evaluated groundwater deficits and surpluses beneath the Nipomo Mesa for the period from 1975 to 1995 using both the specific yield-change in water level method and estimates of difference between inflow and outflow (water budget). Cumulative loss of groundwater storage over the twenty years is 7,000 AF using the change in water level method, and 11,000 AF using the water budget method. For a similar time period, 1976 to 1992, Cleath and Associates (1996a) estimated that volume of Nipomo Mesa groundwater in storage above sea level decreased from 55,200 to 49,200 AF, a net deficit of 6,000 AF, which is similar to the estimated deficits reported by DWR. Note however, that the Addendum to the DWR 2002 report includes an update using data for 2000, and as a consequence of rise in water levels between 1995 and 2000, the DWR analysis indicates zero net change in groundwater storage beneath Nipomo Mesa for the 25-year period from 1975 to 2000.

Based on the data and calculations for the period from 1975 to 1995, DWR (2002) estimated that dependable groundwater yield beneath Nipomo Mesa is in the range of 4,800 to 5,000 AF/Y. DWR also reported that projected groundwater demand for the Nipomo Mesa area exceeds the estimated dependable yield by approximately 50% in 2010, and 80% in 2020. As consequence of an expected decline in water levels, the hydraulic gradient would increase toward Nipomo Mesa from Santa Maria River Valley and the rate of groundwater influx would increase. However, DWR cautioned that increased groundwater flow from Santa Maria River Valley “might not be a desirable long-term solution to meet the water supply needs of the Nipomo Mesa.”

Water budget estimates reported by DWR (Table 26, 2002) indicate that subsurface influx of groundwater to Nipomo Mesa from the Santa Maria River Valley accounts for about 35% of the total inflow of water for Nipomo Mesa (including rainfall). Groundwater modeling by Cleath and Associates (1996a) of increased pumping associated with Nipomo Mesa development projects indicates that approximately half of the increased groundwater

extraction at Nipomo Mesa comes from Santa Maria River Valley and ultimately recharge from the Santa Maria River. A more detailed discussion and analysis of the water budget estimated by DWR for Nipomo Mesa follows.

### 3.4 Estimates of Groundwater Demand and Capacity

DWR (2002) reported annual estimates of water budget for Nipomo Mesa for the period from 1975 to 1995, and for future years 2010 and 2020. Estimated components of inflow include

- deep percolation of precipitation;
- urban return;
- agricultural return;
- other return (zero for Nipomo Mesa);
- recharge of recycled water;
- subsurface inflow from Santa Maria River Valley and Nipomo Valley.

Estimated components of outflow include

- urban, agricultural, and other groundwater extraction;
- subsurface outflow to Tri-Cities Mesa – Arroyo Grande Plain; and
- subsurface outflow to the Ocean

Chapter 7 in the DWR report includes a discussion of each of these water budget components, and DWR Table 26 lists the annual values for each component for the period from 1975 to 1995, as well as for 2010, and 2020. Figure 14 illustrates the average contribution of each of the inflow and outflow components for DWR's Nipomo Mesa water budget estimates. DWR selected water years 1984 to 1995 as the base period for their evaluation. This period encompassed the most recent pair of wet and dry trends.

Figure 15-A shows DWR's estimated annual values for total inflow and outflow for Nipomo Mesa for the 20-year period from 1975 to 1995 and projected estimates for years 2010 and 2020. Average annual inflow during the study base period (1984-1995) is also shown on the graph (Figure 15-A). This graph shows that DWR's estimates of total outflow have exceeded average inflow since 1980 with an apparent increase in deficit with time.

Figure 15-B is a graph showing more detail of the DWR (2002) water budget annual estimates (see also Figure 14). The annual value of deep percolation component of inflow varies greatly because it is a function of rainfall. Components of inflow other than deep percolation (60 percent of which is groundwater inflow from Santa Maria River Valley) are more stable and show two nearly flat trends during the 20-year period of analysis: (1) 1975 to 1985 and (2) 1986 to 1995. We have fitted a line through these data and the DWR estimates for 2010 and 2020. This suggests a 1000 AF per decade increase (12.5 percent) in inflow to groundwater beneath Nipomo Mesa other than deep percolation of rainfall and accounts for increase subsurface inflow in response to increasing hydraulic gradient toward Nipomo Mesa with increases in pumping.

Figure 15-B also shows a trend line fitted to the 20-year period of outflow values to provide an estimate of outflow rates in the future. The trend increases at a rate of 1.2% per year. DWR's estimated values of outflow for years 2010 and 2020 are close to this projected trend. Also shown on Figure 15-B (open diamond symbols) are estimates of Nipomo Mesa water demand for years 2002 and 2020 from the County Master Water Plan Update (January, 2003) discussed in Section 3.5 below. These two demand estimates by the County (9.2 AF/yr in 2002 and 12.6 AF/yr in 2020) equate to an increase of 1.75% per year. The filled diamond symbols at 2002 and 2020 are the County's Nipomo Mesa Demand estimates with the DWR estimates of subsurface outflow added (Table 26, DWR, 2002).

We used trends and averages of the DWR water budget components to project two ranges of estimated inflow to Nipomo Mesa. These and the projected outflow are shown on Figure 15-C. One inflow range is constant with time. The lower value (6,800 AF/yr) is based on the DWR average inflow estimate for their base period: 1984-1995 (Table 26, DWR, 2002). The upper value (7,800 AF/yr) is based on average deep percolation for the 20-year period from 1975-1995, which is greater than the DWR base period (1984-1995), and average inflow (excluding deep percolation of rainfall), during the period from 1986 to 1995 (Table 26, DWR, 2002), which is the higher other inflow plateau shown on Figure 15-B.

The other inflow range shown on Figure 15-C increases with time. The rate of increase is based on the trend line fitted to the DWR estimates of components of inflow, not including deep percolation, for the period 1975-1995 and including the estimated values for years 2010 and 2020. This trend line and the data are shown on Figure 15-B. Addition of the average value of deep percolation for the DWR base period (1984-1995) gives the bottom of the increasing inflow range. And, addition of the average value of deep percolation for the 20-year period (1975-1995) gives the top of this increasing inflow range.

This analysis of the DWR water budget estimates for Nipomo Mesa shows outflow outpacing inflow even if we account for estimated increasing influx of groundwater from Santa Maria River Valley due to increasing pumping beneath Nipomo Mesa. By year 2025, estimated outflow exceeds the highest of a range of inflow estimates by 20 percent (Figure 15-C)—substantial overdraft and mining of groundwater in storage, and accompanying reduced production capability from many wells, increased energy costs for pumping, reduction of groundwater discharge to the coastal drainages and lakes west of Nipomo Mesa, and increased risk of seawater intrusion of the aquifers near the coastal margin.

### **3.5 Nipomo Water-Planning Area**

The first phase of the San Luis Obispo County's Master Water Plan Update defined twelve Water Planning Areas (WPA) that are based on geography and land use (EDAW

and Boyle, 1998). The County addresses water supply and demand separately for each WPA. The Nipomo Area (WPA 6), which is one of six coastal water-planning areas in the County, includes the southern portion of the County. To better address specific water needs, the second phase of the Master Water Plan Update divided WPA 6 into four geographic water-demand sub-regions: Nipomo Mesa, Nipomo Valley, which is east of Hwy 101, the Suey Creek Area, which is further southeast, and the portion of the Santa Maria River Valley in San Luis County (north of the Santa Maria River). Figure 2 illustrates the subareas of WPA6.

Nipomo Community Services District (NCSD) and the Southern California Water Company (SCWC) are the primary municipal water purveyors in WPA 6. In addition there are approximately 25 private water purveyors that pump groundwater beneath WPA 6. In addition, there are hundreds of private domestic wells.

Estimates by the County (January 2003a) of current and projected water demand for the Nipomo Mesa sub region of WP6 (Figure 2) are summarized in the table below. Estimates of urban demand provided by the table only include water provided to customers serviced by NCSD and SCWC. These estimates are based on NCSD and SCWC records and projections.

**Table 2**  
**Summary of Estimates by the County of Water Demand for Nipomo Mesa**

| Category of Demand | Year 2002<br>(1000 af/yr) | Projected Demand<br>Year 2020 or Build Out<br>(1000 af/yr) |
|--------------------|---------------------------|--|
| Urban              | 3.9                       | 7.34   |
| Agricultural       | 2.9                       | 1.9  |
| Rural              | 2.42                      | 3.35   |
| Environmental      | 0                         | 0  |
| Total              | 9.22                      | 12.59  |

Considerable effort by the County and consultants went into the estimates of agricultural demand, which is also called Gross Irrigated Water Requirements (GIWRs) in the County Master Water Plan Update document. The estimates incorporate assessment of acreages of various crop types, evapotranspiration, effective rainfall, frost protection, leaching requirements, and irrigation efficiency. In the 2003 Update for WPA 6 (San Luis Obispo County, 2003a), the County reported a range of agricultural demand: 2,400 to 3,580 AF in 2002, and 1,440 to 2,280 AF in 2020. The average of each range is provided in Table 1 above.

Rural water demand includes rural dwelling units, schools, churches, and some commercial and industrial facilities, irrigation water for the Black Lake and Cypress Ridge golf courses, and the proposed Woodlands Development. It includes water provided by purveyors other than NCSD or SCWC as well as private domestic wells.

Because most private wells are not metered, rural water demand was estimated by number of dwelling units (DU) and parcel size. Duty factors were 0.5 AF/DU/YR for homes on less than one acre, 1.5 for homes on more than an acre, and 2 AF/ACRE/YR for golf courses. The County used estimates of 1550 dwelling units in 2002, and 2,300 at build-out.

Environmental demands include conditions on water right permits and licenses and associated orders by the State Water Resources Control Board, California Fish and Game, and other regulatory agencies. No current environmental demands are in place, and the County assumed none for 2020. However, the possibility exists that future environmental demands for Nipomo Mesa could be put in place to help ensure minimum discharges to Black Lake Canyon and the lakes and coastal watersheds west of the mesa.

### **3.6 Groundwater Modeling to Assess Impact of Development**

Despite concern that recent and proposed residential developments of the Nipomo Mesa may accelerate the depletion of groundwater storage and degrade the quality of groundwater near the coast by inducing salt-water intrusion, some hydrogeologic evaluation and groundwater modeling reports (e.g. Cleath and Associates, 1996a, 1997; 1998; ESA 1998) assert that the impact of additional pumping for proposed development is insignificant. However, for several reasons some of the model results may underestimate the future groundwater declines and overestimate sustainable yield:

- Typically, the model runs to estimate potential future impact of a project were conducted by adding increased pumping associated with a proposed development, but the rest of the pumping assigned in the model remained constant for model simulations, 48-years into the future. This does not account for cumulative impact of projected increased future groundwater demand for other portions of Nipomo Mesa and the Santa Maria River Valley and underestimates future water budget deficits.
- No model simulations are presented with long periods with less than average rainfall.
- After the Woodlands model was developed, information became available indicating that Eucalyptus Globulus trees have dense mat of shallow roots that store excess water and use 80-90 % of rainfall. Since the majority of 863 acres of these trees would be removed for the development project, the model runs to estimate potential impact to groundwater were revised to reflect increased recharge of rainfall to groundwater after removal of the eucalyptus trees. However, apparently the base case model was not revised using reduced recharge before removal of the trees. This revision would likely require recalibration and local reduction of hydraulic conductivity resulting in increased groundwater drawdown associated with additional pumping.
- The model may not adequately account for interception and diversion of infiltrating water by low-permeable intervals within both the Nipomo Mesa dunes and upper portion of the Paso Robles Formation. Consequently the model may overestimate recharge to the main aquifer beneath Nipomo Mesa.



Hydraulic conductivity values assigned in the Cleath and Associates model (Cleath and Associates, 1996a, 1997; 1998; ESA 1998) along the coastal margin and along the Santa Maria River are significantly higher than available estimates from pumping tests and higher than values assigned to the Santa Maria Basin model (Luhdorff & Scalmanini, 2000). Particularly high values are assigned in the vicinity of Black Lake and the northwest corner of the model domain. The resulting model transmissivity (hydraulic conductivity times aquifer thickness) near the coast west of Nipomo Mesa is 9 times higher than in the Santa Maria Basin Model and 19 times higher than values used by DWR for water balance calculations. As a consequence, the model groundwater discharge rates to the sea may be as much as ten times too high and the decreases in groundwater levels toward the coast due to increases in pumping beneath Nipomo Mesa, perhaps ten times too low.

### 3.7 Sea Water Intrusion

The aquifer system of Nipomo Mesa and the Santa Maria Groundwater Basin is hydraulically continuous offshore beneath the ocean. In a typical coastal aquifer, freshwater discharges from the seafloor to a point where the interface between freshwater and saltwater intersects the seafloor. The interface slants inland and downward and its geometry is controlled by density differences, hydraulic gradient within the freshwater portion of the aquifer, and distribution of hydraulic conductivity of the aquifer system. Figure 16 shows a conceptual model of a freshwater-saltwater interface for an idealized homogeneous coastal aquifer.

#### 3.7.1 Idealized Freshwater/Saltwater Interface

Assuming steady-state horizontal flow in the freshwater (brackish) region and no flow in the saltwater region, the estimated depth below sea level of a sharp freshwater-saltwater interface in a confined aquifer can be calculated with the following equation (p. 385, Bear, 1979):

$$h_s = [P_f / (P_s - P_f)] h_f$$

where  $h_s$  is the depth to the interface below sea level,  $P_f$  is the density of the freshwater,  $P_s$  is the density of the seawater, and  $h_f$  is the freshwater head. For density values of 1 g/cc for fresh water and 1.025 for seawater the equation is:

$$h_s = [1 / (1.025 - 1)] h_f = 40 h_f$$

For a typical hydraulic gradient of 0.00143 between the Nipomo Mesa and the coastline we calculate saltwater interface in an idealized homogeneous aquifer as shown on Figure 17. If the depth of the freshwater/saltwater interface is known near the coastline, Figure 17 provides insight to the hypothetical distance offshore of the freshwater/saltwater groundwater interface. Reports of poor groundwater quality in the Careaga Sands at depths greater than 700 feet near the coast (e.g. Dames and Moore, 1991) would suggest that the offshore interface might intersect the seafloor at a distance on the order of 12,000 feet.

### *3.7.2 Coastal Margin Monitoring Wells*

In the 1960s and 70s, a total of seven monitoring wells were installed near the coast to monitor hydraulic head, water quality, and test for evidence of salt water intrusion, and provide an early warning if saltwater intrusion reaches the coastline. Figure 18 shows the location of the coastal margin monitoring wells that serve as sentries for salt-water intrusion. Most of these monitoring wells consist of several piezometers screened at different depths.

Water samples collected twice per year from these wells show no clear evidence of salt-water intrusion. Generally the hydraulic gradient has remained westward near the coast. However, concern regarding potential for salt-water intrusion is based on interpretation that the Careaga Sand is exposed on the sea floor several miles west of the coastline, and there are no known barriers to salt water intrusion.

With the exception of a couple of the shallow screens, which either have poor seals between the surface or intercepted local perched brackish water, chloride concentrations in all of the piezometers are well below the MCL of 250 mg/l for chloride in drinking water, which is nearly two orders of magnitude less than the concentration of chloride in sea water (20,000 mg/l).

The two highest concentrations of chloride in deep piezometers are 95 mg/l at a depth of 720-730 in monitoring well 11N/36W-12C, which is on the coastline west of Black Lake, and 125 mg/l at depth of 535-545 in MW 12N/36W-36L, which is a couple of miles further north. These relatively elevated chloride levels might be indicative of shoreward advancement of the seawater interface. Approximately 2.5 miles inland, groundwater levels in production well 11N35W20E001S, which is southwest of Nipomo Mesa, were pumped down to 40 feet below sea level in the 1940s to 1950s, and down to 80 feet below sea level for several years in the early 1970s (Figure 19). Potential seawater intrusion as a consequence of this pumping may occur beneath the coastline several decades after this pumping. Groundwater modeling discussed below helps to assess likely lag-times between inland pumping and potential seawater intrusion of the aquifer.

### *3.7.3 Modeling to Evaluate Potential Salt Water Intrusion*

We developed groundwater flow and chemical transport models for use as tools to help evaluate potential seawater intrusion. Specifically, the models were used to evaluate time lapse between heavy inland pumping and changes in aquifer hydraulic head, groundwater discharge, and increases in groundwater salinity in the aquifer beneath the coastal margin. Summary descriptions of the model designs are provided in Appendix D.

Results of a simplistic MODFLOW/MT3D (McDonald and Harbaugh, 1988; Zheng, 1990, 1999) flow and transport model show a lag time of many decades between the onset of pumping 15,000 feet inland and increase in chloride concentration in groundwater beneath the coastal margin even when pumping only lasts for 5 years (Figure 20). For this model, however, the initial position of the freshwater/saltwater interface is assumed to be



coincident with the sea floor. If the interface were further inland, the increase in salinity would occur more rapidly.

A second set of models was run using SEAWAT (Guo and Langevin, 2002), which is a specialized version of MODFLOW/MT3D that also accounts for variable fluid density. Appendix D provides a summary of the SEAWAT modeling. Model inflow includes constant head at upland margin and uniform recharge of 4 inches per year (25% of average rainfall).

First, the model was run without any pumping to achieve an equilibrium position for the saltwater-freshwater interface. Then a range of pumping rates were simulated at a distance of 15,000 feet inland using the non-pumping equilibrium initial condition for each case. Figure 21 shows a series of cross-sections of a coastal margin aquifer that illustrate the model equilibrium salinity distribution for a range of pumping rates. These model results show significant saltwater intrusion when the pumping rate exceeds 60% of the total inflow.

Figure 22 shows model increase with time of salinity in groundwater for a range of depths at distance of 3000 feet from the coastline as a consequence of pumping 15,000 feet inland at 70 percent of the total inflow. The model pumping well is screened between 100 and 600 feet below the static water table.

The models are simplistic tools and do not account for heterogeneity of hydraulic conductivity in the aquifer system that we know occurs. Relatively high permeability preferential pathways could exist within the aquifer and result in saltwater intrusion occurring more quickly than the models suggest. On the other hand, the two-dimensional cross-section nature of the modeling overestimates the response beneath the coastline to inland pumping because the model design does not allow for any groundwater inflow from the north or south. This is equivalent to assuming that uniform pumping occurs all along the coast and no groundwater flow occurs parallel to the coastline.

The model results are not intended to represent reality, or to predict the future, but they help evaluate time frame and sensitivity with depth for potential increases in salinity associated with seawater intrusion. For example, the models results suggest that drawdown of water levels to 80 feet below sea level due to heavy pumping a few miles inland 30 years ago, may still result in saltwater intrusion in the future. The modeling also suggests that pumping rates less than 50 percent of the total inflow (from percolation and subsurface flow) may not lead to significant degradation of groundwater quality in the coastal aquifer, but that pumping rates exceeding 50 percent of the total inflow may. In addition, pumping can induce upward flow of saline groundwater at depth.

## **Section 4**

### **Conclusions and Recommendations**

Evaluation of long historical records of groundwater levels and rainfall in the Santa Maria River Valley indicates that a 25-year period (1945-1970) with 2 inches less than average annual rainfall resulted in major decline of groundwater levels in the Santa Maria River Valley. Based on the 117-year rainfall record, the probability is approximately 30 percent that a 10-year period with 2 inches less than average annual rainfall will occur in the one hundred years resulting in major decline in groundwater levels again in the Santa Maria River Valley. Because of increased groundwater demand compared to the period from 1945 to 1970, the depletion of groundwater storage and resulting problems would likely be greater than before.

The aquifer system beneath Nipomo Mesa is contiguous with the Santa Maria River Valley and groundwater flow from the Santa Maria River Valley toward Nipomo Mesa constitutes a significant portion of the inflow to the Nipomo Mesa groundwater budget (including rainfall). Reported estimates of the contribution from Santa Maria River Valley range from approximately 35 percent (DWR, 2002) to 50 percent (Cleath & Associates, 1996a). A major decline of groundwater levels in the Santa Maria River Valley would decrease subsurface inflow to the Nipomo Mesa area.

Estimates by DWR (2002) of water budget deficits for the Nipomo Mesa Area during the period from 1975 to 1995 appear to be reasonable and agree well with a deficit estimated for a similar time period by Cleath and Associates (1996a). While modeling by Cleath and Associates (1996a, 1997, 1998, 2001) may provide reasonable assessments of future additional impact to groundwater by a development project, some of the model simulations do not provide realistic estimates of future groundwater conditions because the future simulations have neither provision for increased demand elsewhere in the basin, nor prolonged periods with less than average rainfall. Assigned transmissivity along the coastal margin in the Cleath and Associates model appears to be substantially too high and likely results in underestimates of water level decline near the coast and potential for saltwater intrusion. Decrease of transmissivities assigned to the model near the coast, incorporation in the model of projected general increases in demand for other portions of the groundwater basin in addition to specific proposed projects, and simulations designed to evaluate the effect of a series of several years with less than average rainfall would help to improve the model as a tool to assess the groundwater resource capacity of Nipomo Mesa.

Although the highly permeable dune deposits of Nipomo Mesa facilitates a high rate of infiltration of rainfall on the Mesa, fine-grained intervals within the dunes and in the upper portion of the Paso Robles Formation intercept a portion of the deep percolating water. This perched groundwater flows along these low-permeability layers and discharges into Black Lake Canyon and the other systems of coastal drainages and lakes west of Nipomo Mesa. Groundwater modeling and water budget calculations that neglect discharge of the

perched shallow groundwater likely overestimate recharge rates to the main aquifer beneath Nipomo Mesa.

The DWR 2002 report “*refrains from finding that the Santa Maria Groundwater Basin within San Luis Obispo County is currently in overdraft because of consistent subsurface outflow to the ocean and no evidence of sea water intrusion*” (pg 155, DWR, 2002). This statement by DWR is inconsistent with their definition of overdraft (e.g. pg 154 DWR 2002): “*the condition of a groundwater basin or subbasin in which the amount of water withdrawn by pumping exceeds the amount of water that recharges the basin over a period of years, during which water supply conditions approximate average conditions.*” Based on this definition, since current and projected pumping beneath Nipomo Mesa exceeds inflow (recharge plus subsurface inflow), the Nipomo Mesa portion of the Santa Maria Groundwater Basin is currently in overdraft and projections indicate increasing overdraft.

By year 2025, projection of outflow exceeds the highest of a range of inflow estimates by 20 percent. This substantial overdraft and mining of groundwater in storage, will likely be accompanied by reduced production capability from many wells, increased energy costs for pumping, reduction of groundwater discharge to the coastal drainages and lakes west of Nipomo Mesa, and increased risk of seawater intrusion of the aquifers near the coastal margin.

DWR’s (2002) reported finding of “*consistent subsurface outflow to the ocean and no evidence of sea water intrusion*” does not preclude the existence of overdraft conditions. DWR’s definition of overdraft, which is provided two paragraphs above, is simply that pumping exceeds recharge over a period of years with approximately average conditions. Indeed it is possible for consistent subsurface outflow to the ocean to persist for decades despite concurrent overdraft conditions in an inland portion of the same groundwater basin. In addition, although we agree that seawater intrusion is not yet evident based on data from the coastal monitoring wells, the basis for consistent subsurface outflow from the aquifers to the ocean is tenuous. The DWR’s water budget analysis for the Nipomo Mesa area (Table 26, DWR 2002) indicates that for both the base study period (1984-1995) and for 2020 projections the best estimate of subsurface outflow to the ocean is in the range of only 8 to 9 percent of the total inflow including recharge from average rainfall. This indicates that consistent subsurface outflow to the ocean from the aquifers beneath the Nipomo Mesa Area is vulnerable to small proportional increases in groundwater withdrawal from Nipomo Mesa, or reductions in inflow, for example a prolonged period of low rainfall or increased pumping in Santa Maria Valley.

DWR’s (2002) conclusions for the Nipomo Mesa area study seem to confuse assessment of water resource capacity and manifestation of exceeding dependable yield. The DWR analyses, projections, and water budget estimates clearly indicate that groundwater pumping in the Nipomo Mesa area is in excess of the dependable yield and that overdraft conditions have existed and are expected in the future. Our analyses indicate that as a consequence of the buffering effect of depletion of groundwater in storage and slow rates

of groundwater flow in the aquifers, a lag time of several decades is expected before overdraft conditions are manifested as seawater intrusion in the aquifers near the coast. Reduction of groundwater discharge to coastal drainages and lakes west of Nipomo Mesa is likely to be a relatively rapid consequence of continued overdraft conditions beneath the Nipomo Mesa.

The County's Resource Management System (RMS) defines three categories of levels of severity when water supply is exceeded by demand<sup>8</sup>. Based on a January 2000 draft version of the DWR report on the water resources of the Nipomo Area (DWR, 2002), the County General Plan recommended a Water Supply Level of Severity of II for the Nipomo Mesa Sub-Unit of the Santa Maria Groundwater Basin.

Analysis of the groundwater budget estimates reported by DWR (2002) for Nipomo Mesa shows outflow outpacing inflow (including estimates of recharge from average rainfall) since 1980. Projections to year 2025 show an increasing deficit, even when accounting for increasing influx of groundwater from Santa Maria River Valley due to increasing pumping beneath Nipomo Mesa. By year 2025, the estimated outflow exceeds even the highest of a range of inflow estimates by 20 percent. Thus, DWR's findings are consistent with a Level of Severity III RMS Water Supply Criterion for groundwater beneath the Nipomo Mesa Area.

Although existing and projected future water demand at Nipomo Mesa exceeds sustainable groundwater supply based on local water balance analyses, associated potential impact such as seawater intrusion of the aquifer system is not an imminent threat.

Reliable prediction of when seawater intrusion will significantly impact quality of water pumped from wells near the coastal margin is impossible. Important unknowns include

- historical and current location of the interface between freshwater and seawater in the aquifers offshore,
- when did/will the seawater intrusion clock start ticking? 1940s, 1970s, 2000?
- offshore aquifer geometry and degree of hydraulic connection between aquifers and the sea,
- high permeability preferential pathways for sea water intrusion such as faults or ancient river channel deposits.

Groundwater models cannot serve as crystal balls, but when designed as tools to assess implications of reasonable possibilities they are useful to evaluate alternatives for groundwater management and potential timing of seawater intrusion. A groundwater model developed as a resource management tool could also be used to assess possible progression of seawater intrusion.

---

<sup>8</sup> County RMS water supply levels of severity:

I projected demand over the next nine years equals or exceeds estimated dependable supply.

II projected demand over the next seven years equals or exceeds estimated dependable supply.

III existing demand equals or exceeds the dependable supply.

Estimates of hydraulic gradient and changes in groundwater storage using water level contour maps by DWR (2002) are difficult to evaluate because the data points on which the contours are based are not included and the screen intervals and pumping status of the wells is not provided. Recent completion of work by the County on compiling historical data and upgrading the database of groundwater elevations will facilitate routine evaluation of hydraulic gradients and change in groundwater storage. Collaboration with Santa Barbara County to collect semi-annual water level data and produce annual monitoring reports is recommended to improve understanding to Santa Maria Groundwater Basin as a whole.

Continued efforts on Nipomo Mesa to increase the use of recycled water, such as for the irrigation of golf courses, will help to lessen impact of development on the rate of depletion of groundwater resources. Opportunities for conjunctive use of surface water and groundwater on the Nipomo Mesa are limited and expensive because of the lack of significant surface water on the Mesa and the distance and lift that would be required to pipe water in from outside the Mesa. Management of floodwater discharge from Cuyama River to the Santa Maria River with Twitchell dam has provided some enhancement of recharge to the aquifers of the Santa Maria River Valley. However, since water in the Santa Maria River nearly always infiltrates the subsurface before reaching the coast, there is little opportunity for additional enhancement of recharge along the river without an additional source of water. Basin management planning should also account for likely future decrease in recharge enhancement provided by flood water management at Twitchell Dam due to depletion of Cuyama river flows by heavy groundwater pumping in Cuyama Valley (DWR, 2003) and decrease in storage capacity with accumulation of sediment in Twitchell Reservoir (e.g. SAIC et al., 2003).

Importation of water to Santa Barbara County from the State Water Project (SWP) began in 1996; approximately 12,000 AF of SWP water were provided to the Santa Maria Groundwater Basin in 1999. Continued supply of SWP to the Santa Maria River Valley is important to help offset groundwater supply deficits for portions of both Santa Barbara and San Luis Counties. Perhaps the two Counties can work together to increase the SWP allotment to the Santa Maria River Valley. Desalinization of seawater is also an option for supplementary water supply for Nipomo Mesa, but is generally considered a very expensive, last resort option.

Water conservation measures and appropriate limits on development of the coastal communities are perhaps the most practical approaches for preventing sustained depletion of groundwater resources of Nipomo Mesa and the Santa Maria Groundwater Basin as a whole.

## Section 5 References

- Alley, W.M., T. Reilly, O.L. Franke, 1999, Sustainability of Ground-Water Resources, U.S. Geological Survey Circular 1186, 79 pgs.
- Arthur D. Little et al., 1998, Guadalupe Oil Field Remediation and Abandonment Project, Final Environmental Impact Report, prepared for SLO County Dept of Planning and Building, March 1998.
- Bredehoeft, J., S.S. Papadopoulos, and H.H. Cooper Jr., 1982, The Water Budget Myth, *in* Scientific Basis of Water Resource Management, Studies in Geophysics, 51-57, Washington DC: National Academy Press.
- Bredehoeft, J., 1997, Safe yield and the water budget myth: Ground Water, v. 35, no. 6, p. 929.
- Bredehoeft, J., 2002, The Water Budget Myth Revisited: Why Hydrogeologists Model: Ground Water, v. 40, no. 4, p. 340-345.
- California Department of Water Resources, 1970, Sea-Water Intrusion: Pismo–Guadalupe Area: Bulletin No. 63-3, 76 p.
- California Department of Water Resources, 1979, Ground Water in the Arroyo Grande Area: Southern District Report, June 1979.
- California Department of Water Resources, 1998, California Water Plan Update: Bulletin 160-98.
- California Department of Water Resources, 2000, Water Resources of the Arroyo Grande-Nipomo Mesa Area, Revised Final Draft, January 2000.
- California Department of Water Resources, 2002, Water Resources of the Arroyo Grande-Nipomo Mesa Area; Southern District Report.
- California Department of Water Resources, 2003, California's Groundwater, Bulletin 118, Update 2003, October 2003, 246 p.
- California Regional Water Quality Control Board, Central Coast Ambient Monitoring Program (CCAMP), regionally scaled water quality monitoring and assessment program, <http://www.ccamp.org/ccamp/ccamp.htm>
- Chipping Geological Services, 1994, Black Lake Canyon Geologic and Hydrologic Study, Draft: Los Osos, California.
- Cleath & Associates, 1994, Well Construction Report for the Woodlands :Project, *prepared for* Hanson Properties West, Inc., September 1994.



- Cleath & Associates, 1995, Ground Water Supply Management for Bartleson Development Plan, Project, *prepared for* Stuart Bartleson, July 1995.
- Cleath & Associates, 1996a, Water Resources Management Study for The Woodlands, *prepared for* USI Properties, Inc., April 1996.
- Cleath & Associates, 1996b, Status of the Santa Maria Ground Water Basin, *prepared for* USI Properties, Inc., April 1996.
- Cleath & Associates, 1997, Water Resources Management Study addendum for the Woodlands, *prepared for* USI Properties, Inc., September 1997.
- Cleath & Associates, 1998, Modeling Data and information for the Woodlands Project, Woodlands Specific Plan EIR: San Luis Obispo, California, *prepared for* San Luis Obispo County, June 9, 1998.
- Cleath & Associates, 2001, Ground water impact of the 180 units of development projects identified by the County of San Luis Obispo on Nipomo Mesa, *prepared for* PH Properties, Inc., April 17, 2001.
- Cleath & Associates, 2003, Water and Wastewater impacts analysis for Summit Station Area Land Use Ordinance Amendment, prepared for EMC Planning Group, Inc., October, 2003.
- Dames & Moore, 1991, Draft Program Environmental Impact Report, Groundwater Resources Section, Conservation Element, Santa Barbara County Comprehensive Plan, October, 1991.
- EDAW and Boyle Engineering, 1998, Master Water Plan Update, San Luis Obispo County, Phase I; August 1998.
- Envicom Corporation, 1982, Development Constraints Analysis, Black Lake Gold Course, San Luis Obispo County, California: Calabasas, California, *prepared for* San Luis Obispo County.
- Envicom Corporation, 1982, Final Environmental Impact Report, Black Lake Specific Plan, *prepared for* San Luis Obispo County, December 3, 1982.
- Envicom Corporation, 1985, Final Environmental Impact Report, Bjerre General Plan Amendment.
- Environmental Science Associates, 1996, Final Woodlands Specific Plan, Baseline Environmental Assessment and Constraints Analysis: Los Angeles, California.
- Environmental Science Associates, 1998, Woodlands Specific Plan, Supplemental Environmental Impact Report: Los Angeles, California, *prepared for* the San Luis

- Obispo County Department of Planning & Building, September 1998 (Also separate appendices volume).
- Environmental Science Associates, 2001, Woodlands Specific Plan, Supplemental Environmental Impact Report: Los Angeles, California, *prepared for* the San Luis Obispo County Department of Planning & Building.
- Guo, W. and C. D. Langevin, 2002, User's Guide to SEAWAT: A Computer Program for Simulation of Three-Dimensional Variable-Density Ground-Water Flow, *Techniques of Water-Resources Investigations of the US Geological Survey*, Book 6, Chapter A7,
- Heath, R.C., 1989, Basic Ground-Water Hydrology, *USGS Water Supply Paper 2220*, 84 p.
- Hughes, 1977, Evaluation of GW Quality in the Santa Maria Valley, California, US Geological Survey Water Resources Investigation 76-128. 70 p.
- James M. Montgomery Consulting Engineers, Inc., 1982, Ground Water Availability for the Proposed Black Lake gold Course Development Project: Pasadena, California, *prepared for* Plaza Builders, Incorporated.
- Lawrance, Fisk, & McFarland, Inc., 1987, Final Report Water, Wastewater and Drainage Studies, Nipomo Mesa Planning Study, *prepared for* RRM Design Group, August 1987.
- Lipinski, P., 1985, Comparison of two Methods for Estimating Ground-Water Recharge in 1978-80, Santa Maria Valley, California: U.S. Geological Survey Water-Resources Investigations Report 85-4129, *prepared in* cooperation with the Santa Barbara County Water Agency, 17 p.
- Luhdorff & Scalmanini, 2000, Development of a Numerical Ground-Water Flow Model and Assessment of Ground-Water Basin Yield, Santa Maria Valley Ground-Water Basin, *prepared for* Santa Maria Valley Water Conservation District, March, 2000.
- Mann, J.F., Jr., 1961, Factors affecting the safe yield of ground-water basins: *Journal of the Irrigation and Drainage Division, Proceedings of the American Society of Civil Engineers*, v. 87, no. IR3, p. 63-69.
- McClelland Engineers, 1987, Supplement and Final Environmental Impact Report, Guadalupe Abalone Culture Facility, *prepared for* San Luis Obispo County Environmental Coordinator, July 1987.
- McDonald, M.G. and A.W. Harbaugh, 1988, A Modular Three-Dimensional Finite Difference Ground-Water Flow Model, *Techniques of Water-Resources Investigations*, 06-A1, U.S. Geological Survey, 576 p.
- Miller, G.A., and Evenson, R.E., 1966, Utilization of Ground Water in the Santa Maria Valley Area, California: U.S. Geological Survey Water-Supply Paper 1819-A, 24 p.



- The Morro Group, 1990, Appendix A, review of groundwater conditions in the northern Santa Maria Basin and scenarios for the evaluation of impacts of development on the water resources of Nipomo Mesa: *in* The Morro Group, 1991, Final Environmental Impact Report, South County Area Plan Inland Portion: *prepared for* the Office of the Environmental Coordinator, County of San Luis Obispo, p. A1-A59.
- The Morro Group, 1991, Final Environmental Impact Report, South County Area Plan Inland Portion, *prepared for* Office of the Environmental Coordinator, County of San Luis Obispo, May 1991.
- The Morro Group, 1996a, Environmental Assessment of Water Resources Availability, Bartleson Development Plan, *prepared for* County of San Luis Obispo, Department of Planning and Building, January 1996.
- The Morro Group, 1996b, Final Environmental Impact Report, Cypress Ridge Tract Map and Development Plan: *prepared for* the Office of the Environmental Coordinator, San Luis Obispo County, August, 1996.
- Nipomo Community Services District, 1995, A Groundwater Management Plan for the Nipomo Mesa (AB 3030): draft.
- Nipomo Community Services District, 2003, Urban Water Management Plan: draft.
- Santa Barbara County Water Agency, 1994, Santa Maria Valley Water Resources Report, 114 p.
- Santa Barbara County Water Agency, 1996, Draft Groundwater Resources Report, *prepared by* Naftaly et al., *for* Santa Barbara County Water Agency, March 1996.
- Santa Barbara County Water Agency, 1996, Santa Barbara County 1996 Groundwater Resources Report, August 1996.
- Santa Barbara County Water Agency, 1999, Santa Barbara County 1999 Groundwater Resources Report, (incomplete portion of report).
- Santa Barbara County Water Agency, 2000, Groundwater Report, *prepared by* Gibbs et al. *for* Santa Barbara County, February 2001.
- San Luis Obispo County, 2003a, Water Planning Area 6 – Nipomo Mesa, County Master Water Plan Update – Phase II, January 2003.
- San Luis Obispo County, 2003b, Review/Summary of “Water Resources of the Arroyo Grande – Nipomo Mesa”: 2002 Report by DWR, Memorandum to Central File 900.50.01 by Cynthia Koontz, Public Works Department, August 5, 2003.
- Science Applications International Corp (SAIC) et al., 2003, Santa Maria River Estuary Enhancement and Management Plan, prepared for The Dunes Center, The State Coastal

Conservancy, and the Central Coast RWQCB, October 2003, Proposed Final,  
<http://www.dunescenter.org/research.html>

Shipsey & Seitz, Inc., 2002a, Letter to County Planning Commissioners, re PH Property Development Plan S9901187U/T Tract 2341, Date of Hearing: October 24, 2002.

Shipsey & Seitz, Inc., 2002b, Letter to County Board of Supervisors re Woodlands Project, Verification of Water Supply Pursuant to Government Code 66473.7, Mitigation Measure 4.1-6A (Retrofitting), Date of Hearing: December 17, 2002.

Sophocleous, M., 1997, Managing water resources systems: why “safe yield” is not sustainable: *Ground Water*, v. 35, no. 4, p. 561.

Sophocleous, M., 2000, From safe yield to sustainable development of water resources: the Kansas experience: *Journal of Hydrology*, v. 235, pp 27-43.

Thomasson, H.G., Jr., 1951, Surface-water resources: *in* Worts, G.F., 1951, *Geology and Ground-Water Resources of the Santa Maria Valley Area, California*: U.S. Geological Survey Water-Supply Paper 1464, p. 207-223.

Valentine, D.W., Densmore, J.N., Galloway, D.L., and Amelung, F., 2001, Use of InSAR to Identify Land-Surface Displacements Caused by Aquifer-System Compaction in the Paso Robles Area, San Luis Obispo County, California, March to August 1997, U.S. Geological Survey Open-File Report 00-447, 11 p.

Worts, G.F., 1951, *Geology and Ground-Water Resources of the Santa Maria Valley Area, California*: U.S. Geological Survey Water-Supply Paper 1000, 169 p.

Yates, E.B., and J.H. Wiese, 1988, *Hydrogeology and Water Resources of the Los Osos Valley Ground-water Basin, San Luis Obispo County, California*: U.S. Geological Survey Water Resources Investigations Report 88-4081.

Zheng, C., 1990, MT3D, A Modular Three-Dimensional Transport Model for Simulation of Advection, Dispersion, and Chemical Reactions of Contaminants in Groundwater Systems, Report to the U.S. Environmental Protection Agency, Robert S. Kerr Environmental Research Laboratory, Ada, Oklahoma.

Zheng, C., 1999, MT3D<sup>99</sup>, User's Guide, S.S. Papadopoulos & Associates, Inc., Bethesda, Maryland.